



Aug. 30, 2002

FSN 300 tilting spindle Shaper

BASIC MACHINE INCLUDES:

- ◆ Single-phase braking motor, 3.6 HP, 60 Hz
- ◆ Shaper split fence, each micro-adjustable
- ◆ Shaper reversing switch
- ◆ Spindle lock for 0° , -5° , 45°
- ◆ Under table dust collection
- ◆ Overload protection
- ◆ UL Standard
- ◆ CE Standards
- ◆ Service spanners
- ◆ Instruction handbook



TECHNICAL DATA:

Working table size	39 3/8" x 18 3/4"
Shaper speeds	1400-3500-6000-8000 (10,000) RPM
Max. diameter of table opening	8 5/8"
Work spindle diameter (step)	3/4" and 1 1/4"
Spindle tilting	-5° to 45°
Spindle length	5"
Max. spindle stroke	5"
Max. dia. of tool above table	8"
Max. dia. of tool under table	7"
Suction dust hood diameter	4"
Motor	3.6 HP, 60 Hz
Electrical	230V, 1Ø
Net weight	441 lbs.

OPTIONS (Ordered with Machine):

- Three-phase braking motor, 5 HP, 60 Hz \$ 92
- Interchangeable spindle assembly 167
- Chuck for router bits (1/2" chuck, 10,000 RPM) 133

OPTIONS/ACCESSORIES (Available Anytime):

- Sliding table CV1C \$ 575
- Rt. & Lft. table extensions 95
- Tenoning table 47
- Tenoning protection 328
- Extra spindle (3/4", 1", or 1 1/4") 191
- Shaper Fence for round profiles 380
- Shaper Fence with Mori wood presser 47
- Mobility Base (ROJ-D2057) 69
- Shaper cutterhead kit - FH 40 R/1 122
- Shaper cutterhead kit - FH 40 R/4 213



Tech Mark, Inc.
 7901 Industry Drive
 North Little Rock, AR 72117
 PH: 501-945-9393 Fax: 501-945-0312
 Website: www.tech-mark.com