



Aug. 30, 2002

# PT 300 Table Saw

## **BASIC MACHINE INCLUDES:**

- ◆ Three-phase braking motor, 6.25 HP, 60 Hz
- ◆ Integral scoring unit
- ◆ Cut up to 1" dado (w/insert)
- ◆ Rip fence with micro-adjustment
- ◆ 5/8 x 3/4" miter slot
- ◆ Saw guard/suction hood
- ◆ Overload protection
- ◆ UL Standard
- ◆ CE Standards
- ◆ Service spanners
- ◆ Instruction handbook



\* Shown with optional CV2 sliding table.

### **TECHNICAL DATA:**

Max. diameter of main saw blade	12"
Table Size	31 11/16" x 39 3/8"
Main saw arbor	5/8"
Blade tilting	0° - 45°
Speed of main/scoring blade	4340/8340 RPM
Scoring blade arbor	20mm
Scoring saw blade dia.	100mm
Rip Capacity	31 1/2" (52")
Suction dust hood dia.	4"
Electrical	230V, 3Ø
Net weight	814 lbs.

## **OPTIONS (Ordered with Machine):**

- Single-phase braking motor, 3.6 HP, 60Hz \$ 141
- Digital indication of rip fence 999

## **OPTIONS/ACCESSORIES (Available Anytime):**

- Sliding table CV2 (53" crosscut capacity) \$ 859
- Rip extension table (52" rip capacity) 325
- Upgrade Rip Fence (Biesmeyer style) 152
- Carbide scoring blade 100mm (4") 152
- Carbide saw blade 250mm (10") 114
- Carbide saw blade 300mm (12") 133



Tech Mark, Inc.  
 7901 Industry Drive  
 North Little Rock, AR 72117  
 PH: 501-945-9393 Fax: 501-945-0312  
 Website: [www.tech-mark.com](http://www.tech-mark.com)